

ION™ Series



Super-LED® Lighthead

Compact and versatile, Whelen's ION Series lighthead is designed to be utilized in a multitude of applications with numerous mounting options. ION V-Series™ lighthead is available in three-in-one combination or in single color warning models. All new ION DUO™ and TRIO™ lighthead have been re-engineered with linear optics.

ION Family Features

- Hard-coated lenses minimize environmental damage from sand, sun, salt, and road chemicals
- Synchronize to other Whelen sync products
- Go undercover with all new, SAE Class 1 Certified Smoked lenses
- Five year warranty



FEATURES

ION Series

- Single or split color models
- TIR directional or wide-angle light spread models
- Available in universal or surface mount
- Universal mount models include combination permanent/pedestal, clip, edge mounts, and double sided tape, with a Black housing
- Universal mount options include bail/swivel bracket in Black, rubber grommet, and pedestal mount in Black
- Surface mount models includes Black flange
- Single color models have 25 Scan-Lock™ flash patterns
- Split color models have 69 Scan-Lock flash patterns
- 0.40 amps average at 12.8 VDC
- Supplied with 10" 4-wire pigtail
- SAE Class 1 Certified
- Wide-angle surface mount lighthouse, meets NFPA 1901 and KKK-1822F requirements
- Size, Universal Mount: 1" (25mm) H x 1-1/4" (32mm) D x 4" (101mm) L
- Size, Surface Mount: 1-11/16" (43mm) H x 1-1/8" (28mm) D x 5-15/16" (150mm) L



WIONJ
Universal mount



IONB
Universal mount



ION
Smoked lens



IONSMA
Surface mount

MODELS NEW

Universal	
ION*	Red, Blue, Amber, or White
ION#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red, Clear lens
XON*	Red, Blue, Amber, or White, Smoked lens
XON#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red, Smoked lens

Wide-Angle Universal	
WION*	Red, Blue, Amber, or White
WION#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red, Clear lens
WXON*	Red, Blue, Amber, or White, Smoked lens
WXON#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red, Smoked lens

Surface	
IONSM*	Red, Blue, Amber, or White
IONSM#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red, Clear lens
XONSM*	Red, Blue, Amber, or White, Smoked lens
XONSM#	Split Amber/Blue, Amber/White, Blue/Red, or White/Red, Smoked lens

Wide-Angle Surface	
WIONSM*	Red, Blue, Amber, or White
WIONSM#	Split, Amber/Blue, Amber/White, Blue/Red, or White/Red, Clear lens
WXONSM*	Red, Blue, Amber, or White, Smoked lens
WXONSM#	Split, Amber/Blue, Blue/Red, or White/Red, Smoked lens



Replace symbol * in model number with letter indicating color desired: A = Amber, B = Blue, C = White, R = Red
 Replace # symbol in model number with letter indicating split color desired: D=Red/White, E=Blue/White, F=Amber/White, J=Red/Blue, K=Red/Amber, M=Blue/Amber
 For White or Chrome housings, contact factory.

FEATURES

ION DUO & TRIO Series

- Available with DUO (two color interleaved) or TRIO (three color interleaved) technology and new Linear-LED® optics
- Available in Red, Blue, Amber, and White combinations
- Universal mount models include combination permanent/pedestal, clip, edge mounts, and double-sided tape, with a Black housing
- Surface mount models include Black flange
- SAE Class 1 Certified
- Size, Universal Mount: 1" (25mm) H x 1-1/4" (32mm) D x 4" (101mm) L
- Size, Surface Mount: 1-11/16" (43mm) H x 1-1/8" (28mm) D x 5-15/16" (150mm) L

ION DUO

- Supplied with a 10" 5-wire pigtail
- Independent control of color one and color two
- 64 Scan-Lock™ flash patterns

ION TRIO

- Supplied with a 10" 6-wire pigtail
- Choose from any combination of color one, color two, and/or color three
- Color three has steady-burn override feature
- 25 Scan-Lock flash patterns



MODELS NEW

DUO Universal	
I2J	Blue/Red
I2F	Amber/White
I2E	Blue/White
I2D	Red/White
I2M	Blue/Amber
XI2J	Blue/Red, Smoked lens
XI2F	Amber/White, Smoked lens
XI2E	Blue/White, Smoked lens
XI2D	Red/White, Smoked lens
XI2M	Blue/Amber, Smoked lens

DUO Surface	
I2SMJ	Blue/Red
I2SMF	Amber/White
I2SME	Blue/White
I2SMD	Red/White
I2SMM	Blue/Amber
XI2SMJ	Blue/Red, Smoked lens
XI2SMF	Amber/White, Smoked lens
XI2SME	Blue/White, Smoked lens
XI2SMD	Red/White, Smoked lens
XI2SMM	Blue/Amber, Smoked lens

TRIO Universal	
I3JC	Red/Blue/White, White override
I3JA	Red/Blue/Amber, Amber override
I3KC	Red/Amber/White, White override
I3MC	Blue/Amber/White, White override
XI3JC	Red/Blue/White, White override, Smoked lens
XI3JA	Red/Blue/Amber, Amber override, Smoked lens
XI3KC	Red/Amber/White, White override, Smoked lens
XI3MC	Blue/Amber/White, White override, Smoked lens

TRIO Surface	
I3SMJC	Red/Blue/White, White override
I3SMJA	Red/Blue/Amber, Amber override
I3SMKC	Red/Amber/White, White override
I3SMMC	Blue/Amber/White, White override
XI3SMJC	Red/Blue/White, White override, Smoked lens
XI3SMJA	Red/Blue/Amber, Amber override, Smoked lens
XI3SMKC	Red/Amber/White, White override, Smoked lens
XI3SMMC	Blue/Amber/White, White override, Smoked lens

Replace symbol * in model number with letter indicating color desired:
 A = Amber, B = Blue, C = White, R = Red
 Replace # symbol in model number with letter indicating split color desired:
 D=Red/White, E=Blue/White, F=Amber/White, J=Red/Blue, K=Red/Amber, M=Blue/Amber
 For White or Chrome housings, contact factory.

ION V-Series

- Combination models have 180° wide-angle warning, illumination, and puddle light
- Single color models have combination 180° and TIR directional warning
- Available in universal or surface mount
- Universal mount models include combination permanent/pedestal mount, clip, edge mounts, and double-sided tape. Options include bail/swivel bracket in Black or White, pedestal mount in Black or Chrome, and rubber grommet
- Surface mount models include flange, available in Black or Chrome
- Warning segment has 25 Scan-Lock™ flash patterns
- Warning segment available in Red, Amber, Blue, or White
- Six inch pigtail with sync wire allows up to eight lighthead to be synchronized together for the warning segment of the lighthead
- Combination model: Amp draw @ 12 VDC, Warning lights: 0.765/A, Alley lights: 0.31/A, Puddle lights: 0.12/A
- Single color warning model: Amp draw: @ 12 VDC, Warning lights: 1.147/A
- SAE Class 1 Certified
- Size, Universal Mount: 1" (25mm) H x 2-3/16" (56mm) D x 4-1/16" (104mm) L
- Size, Surface Mount: 1-11/16" (43mm) H x 2" (50mm) D x 5-15/16" (150mm) L



MODELS NEW

V-Series Universal		
IONV3*	Combination, Red, Blue, Amber, or White	Black
IONV1*	Single Color, Red, Blue, Amber, or White	Black
XONV3*	Combination, Red, Blue, Amber, or White, Smoked lens	Black
XONV1*	Single Color, Red, Blue, Amber, or White, Smoked lens	Black
V-Series Surface		
IONSV3*	Combination, Red, Blue, Amber, or White	Black
IONSV3*C		Chrome
IONSV1*	Single Color, Red, Blue, Amber, or White	Black
IONSV1*C		Chrome
XONSV3*	Combination, Red, Blue, Amber, or White, Smoked lens	Black
XONSV1*	Single Color, Red, Blue, Amber, or White, Smoked lens	Black

Replace symbol * in model number with letter indicating color desired: A = Amber, B = Blue, C = White, R = Red
 For White housings, contact factory.

ION SERIES OPTIONS

IONK1B	Swivel mount bracket, Black	
IONGROM	Grommet mount kit, Black	
IONPEDB	Pedestal mount kit, Black	
IONBKT1	Universal license plate bracket, horizontal mount, Black	For 2 ION Series lighthead, not for use with ION V-Series
IONBKT2	2013-2016 Ford Police Interceptor Utility, rear hatch mounting brackets (pair), Black	Requires 6 ION Series lighthead, purchased separately
IONBKT4		Requires 2 ION Series lighthead, purchased separately
IONBKT5	Universal mount, reversed. Remove screws without removing the light	
IONBKT6	2015-2016 Chevy Tahoe, rear hatch mounting brackets (pair), Black	Requires 2 ION Series lighthead, purchased separately
IONBKT7	NEW 2015-2016 Chevy Tahoe, grille mount bracket	Requires 2 ION Series lighthead, purchased separately