

V-Series[™] Lightheads

Combination Lighting

Featuring Whelen's innovative optic technology, V-Series Super-LED® lightheads are versatile and efficient. Utilizing multiple planes of light in one lighthead, models are available in a variety of sizes for use in numerous applications. Hard-coated lenses minimize environmental damage from sand, sun, salt, and road chemicals.



SAE 845 Class 1, 180° warning



White steady-burn flood/alley



White ground illumination



ION™ V-Series™





FEATURES

- Combination models have 3-in-1 180° wide-angle warning, illumination, and puddle light
- Single color models have combination 180° and TIR directional warning
- · Available in surface or universal mount
- Surface mount models include Black flange
- · Available in Amber, Blue, Red, and White
- Universal mount includes combination permanent/pedestal, clip, edge mounts, double-sided tape, with a Black housing
- Warning segment has 25 Scan-Lock™ flash patterns
- Six inch pigtail with sync wire allows up to eight lightheads to be synchronized together for the warning segment of the lighthead
- SideKick[™] and Mirror-Beam[™] models include driver and passenger side housings
- Go undercover with SAE Class 1 Certified Smoked lenses
- Combination model: Amp Draw @ 12 VDC, Warning: 0.765/A, Flood: 0.31/A, Puddle: 0.12/A
- Single color warning model: Amp draw @ 12 VDC, Warning: 1.147/A
- Size, Universal mount: 1.02" (26mm) H x
 2.21" (56mm) D x 4.09" (104mm) L
- Size, Surface mount: 1.69" (43mm) H x 1.98" (50mm) D x 5.91" (150mm) L

Warning Certified To:

- SAE J595
- SAE J845

MODELS



Model	Optics	Lens	Mount	Housing/Vehicle
IONV1*		Cloor		Black Housing
IONV1*W	Single Color	Clear		White Housing
XONV1*		Smoked	Universal	Black Housing
IONV3*	0 :- 4	Clear	Ulliversal	Black Housing
IONV3*W	3-in-1 Combination	Glear		White Housing
XIONV3*	Combination	Smoked		Black Housing
IONSV1*				Black Housing
IONSV1*W	Single Color	Clear		White Housing
IONSV1*C	Siligle Color			Chrome Housing
XIONSV1*		Smoked	Surface	Black Housing
IONSV3*			Suriace	Black Housing
IONSV3*W		Clear		White Housing
IONSV3*C				Chrome Housing
XONSV3*		Smoked		Black Housing
SK01V3**		Clear	SideKick	Ford Police Interceptor Sedan,
XK01V3**		Smoked	Fender Mount	2013-2018
VMCT15**		Clear		Chevy Tahoe and
VXCT15**	3-in-1	Smoked		Suburban 1500, 2015-2018
VMDC11**	Combination	Clear		Dodge Charger, 2011-2018
VXDC11**		Smoked		Douge Gharger, 2011-2016
VMFF17**		Clear	Mirror-Beam	NEW Ford Fusion, 2015-2018
VXFF17**		Smoked	Mirror Mount	NEW FOID FUSION, 2013-2016
VMFT11**		Clear		Ford Police Interceptor Sedan,
VXFT11**		Smoked		2013-2018
VMFX11**		Clear		Ford Police Interceptor Utility,
VXFX11**		Smoked		2013-2018

Replace * symbol in model number with letter indicating color desired: A=Amber, B=Blue, R=Red, C=White

IONK1B		Swivel Mount Bracket	
IONGROM		Grommet Mount Kit	
IONPEDB		Pedestal Mount Kit	
IONBKT1		Universal License Plate Bracket for 2 ION lightheads, horizontal mount, not for use with surface mount ION's	
IONBKT2	For IONV	Rear Hatch Mounting Brackets (pair) for 2013-2017 Ford Police Interceptor Utility, for 6 ION's purch. sep.	
IONBKT4	Universal Mount Lighthead	Rear hatch brackets (pair), 2013-2017 Ford Police Interceptor Utility, for two ION's purchased separately	Black
IONBKT5	Only	Universal Mount, reversed, allows access to mounting screws without removing the light	
IONBKT6		Rear hatch brackets (pair), 2015-2018 Chevy Tahoe, requires two ION's lightheads purchased separately	
IONBKT7		Grille mount brackets (pair) for 2015-2018 Chevy Tahoe, requires four ION's lightheads purchased separately	



LINV2™ & LINSV2™ V-SERIES™



LINV2C



Smoked



FEATURES

- Models have 2-in-1 combination warning and puddle light
- · LINSV2 lighthead with right angle bracket mounts beneath a side view mirror, push bumper, or under any flat mounting surface. Includes glamour cap
- LINV2 lightheads include surface mount Black flange
- Warning segment has 25 Scan-Lock™ flash patterns
- · Six inch pigtail with sync wire allows up to eight lightheads to be synchronized together for the warning segment of the lighthead
- · Go undercover with SAE Class 1 Certified Smoked lenses
- Amp Draw @ 12 VDC, Warning: 0.75/A, Puddle: 0.12/A
- LINV2 Size: 1.576" (40mm) H x 1.65" (42mm) D x 3.876" (98mm) L
- LINSV2 Size: 1.1" (28mm) H x 2.80" (71mm) D x 2.89" (73mm) L

Warning Certified To:

- SAE J595
- SAE J845 Selective Coverage (Amber)

Model Mount Lens Housing LINV2* Clear Surface Mount LINV2*X Smoked Black LINSV2* Clear **Under Surface Mount**

Replace * symbol in model number with letter indicating color desired: A=Amber, B=Blue, R=Red, C=White

LINSV2*X

LINV2 Lighth	ead Only	
RFLANGEC	Flange Mounting Kit	Chrome
L6BKT3	46° Push Bumper Bracket, each	Black
RBKT1	"L" Mounting Bracket for 1 Lighthead	Aluminum
RBKT2	"L" Mounting Bracket for 2 Lightheads	Alullillulli
RBKT4	Swivel mounting bracket	Black
RBKT6	License Plate Bracket for 2 Lightheads, Horizontal Mount	
RBKT7	License Plate Bracket for 2 Lightheads, Vertical Mount	
RBKT10	Trunk Mount Bracket for Dodge Charger, pair	Black
RBKT16	Trunk Mount Bracket for 2013-2018 Ford Police Interceptor Sedan, Pair	
LINV2 Lighth Mounting Bra	ead Only - Above or Below the Rear Taillight acket, Pair	
RBKT12	Above Bracket for Ford F-250/350/450/550, 2013-2016	
RBKT14	Above Bracket for Chevy Silverado 1500/ GMC 1500, 2014-2018	Disale
RBKT17	Above Bracket for Dodge Ram, 2014-2018	Black
RBKT18	Above Bracket for Ford F-150, 2015-2018	
RBKT19	Below Bracket for Ford F-150, 2015-2018	
LINSV2 Light	head Only - Under-the-Side View Mirror Mount, Pair	
LSVBKT13	Chevy Silverado 1500/2500, 2014-2018	
LSVBKT34	Ford Police Interceptor Utility 2013-2018	
LSVBKT35	Dodge Charger, 2011-2018	
LSVBKT38	Ford Police Interceptor Sedan 2013-2018	Black
LSVBKT42	Dodge Ram 1500, 2011-2018	DIACK
LSVBKT44	Dodge Durango, 2013-2018	
LSVBKT47	Ford F-150, 2015-2018	
LSVBKT45	Chevy Tahoe and Suburban, 2015-2018	



500 V-Series™



FEATURES

- Combination models have 3-in-1 180° wide-angle warning, illumination, and puddle light
- Single color models have combination 180° and TIR directional warning
- Warning segment has 25 Scan-Lock™ flash patterns
- Six inch pigtail with sync wire allows up to eight lightheads to be synchronized together for the warning segment of the lighthead
- Combination model: Amp Draw @ 12 VDC,
 Warning: 0.12/A, Flood: 1.0/A, Puddle: 0.5/A
- Single color warning model: Amp Draw @ 12 VDC, Warning: 1.5/P, 0.6/A
- Size: 2.13" (54mm) H x 1.64" (42mm) D x 5.39" (137mm) L

Warning Certified To:

- SAE J845
- CAC Title XIII (Blue)





MODELS

5V1*	Single Color Warning
5V3*	3-in-1 Combination

Replace * symbol in model number with letter indicating color desired: A=Amber, B=Blue, R=Red, C=White

• •

5FLANGEB	Elango	Black
5FLANGEC	Flange	Chrome
5FLANGEP	Polished Aluminum Flange	Aluminum
5GROMMET	Rubber Grommet Mount Kit	Black
5GBKT1	"L" Bracket for use with 5GROMMET only	Black
5BKT1	Universal Mount Bracket	Black
5LSMAB	Surface Mount Adapter for Linear Super-LED Only	Black
5LSMAC	Surface Mount Adapter for Linear Super-LED Only	Chrome
5BKT1	Universal Mounting Bracket for 500 Series Super-LED®	Black



V23[™] Series



FEATURES

- Models have 3-in-1 180° wide-angle warning, illumination, and puddle light
- Includes surface mount Black flange
- Warning segment has 25 Scan-Lock[™] flash patterns
- Go undercover with SAE Class 1 Certified Smoked lenses
- Six inch pigtail with sync wire allows up to eight lightheads to be synchronized together for the warning segment of the lighthead
- Amp Draw @ 12 VDC, Warning: 0.76/P, 0.30/A, Flood: 0.62/A, Puddle: 0.12/A
- Size: 2.68" (68mm) H x 1.5" (38mm) D x 4.25" (108mm) L

Warning Certified To:

- SAE J595
- SAE J845 Selective Coverage





MODELS

1/00/200		01 1	D E.
V23*TPB	Combination 180°	Clear Lens	Black Flange
V23*TPC	Warning, Take-Down and Puddle Light	Clear Lens	Chrome Flange
V23*TPBX		Smoked Lens	Black Flange
V23*TPCX	Combination	Smoked Lens	Chrome Flange

Replace * symbol in model number with letter indicating color desired: A=Amber, B=Blue, R=Red, C=White

V23P20B	20° Angled Surface Mount	Black
V23P20C	Housing	Chrome
V23PEDB	Pedestal Mount Kit	Black
V23PEDC	Pedestal Would Kit	Chrome



400 V-Series™

FEATURES

- Models have 3-in-1 180° wide-angle warning, illumination, and puddle light
- Surface mount, supplied with rubber gasket
- Warning segment has 25 Scan-Lock[™] flash patterns
- Six inch pigtail with sync wire allows up to eight lightheads to be synchronized together for the warning segment of the lighthead
- Amp Draw @ 12 VDC, Warning: 1.2/A, Flood: 0.40/A, Puddle: 0.12/A
- Size: 3" (76mm) H x 1.65" (42mm) D x 4.88" (124mm) L

Warning Certified To:

- KKK 1822-F Lower
- CAC Title XIII
- NFPA 1901

M4 V-Series

FEATURES

- Models have 2-in-1 combination warning and perimeter lighting
- Surface mount
- Warning segment has 25 Scan-Lock flash patterns
- Six inch pigtail with sync wire allows up to eight lightheads to be synchronized together for warning segment of the lighthead
- Amp Draw @ 12 VDC, Warning: 1.0/P, 0.40/A, Perimeter: 0.77/A
- Size: 3.38" (86mm) H x 1.85" (47mm) D x 5.5" (139mm) L



MODEL

4V3*	Surface		
Replace * symbol in n A=Amber, B=Blue, C	nodel number with LED color desired: =White, R=Red		\bigcirc

OPTIONS

4FLANGEB	Flange Kit	Black
4EFLANGE	Flange Kit	Chrome
4TSMAB 4TSMAC	Super-LED® Surface Mount Adapter,	Black
	Linear-LED® & Super-LED Only	Chrome
4EGRILB	Grille-Master™ Housing with Swivel	Black
4EGRILP	Bracket	Chrome
4BKT1	Universal "L" Mounting Bracket for 400 Series Lighthead, must be used with 4TSMAB or 4TSMAC Flange	Black



M4V2B

MODEL

M4V2*	Surface	Option	nal Fla	ange		
Replace * symbol in mode	I number with LED color desired:				\bigcirc	

M4FB	Flange	Black
M4FC	Flange	Chrome
M4FC400	Flange, adapts M Series to 400 Series Style	Chrome
M4BRUSH	Brush Guard	Black
4BKT1	Universal "L" Mounting Bracket for M4	Black



M6 V-Series™

FEATURES

- Models have 2-in-1 combination warning and perimeter lighting
- Surface mount
- Warning segment has 21 Scan-Lock[™] flash patterns
- Rear lightbar pods house multiple M6 lightheads for the 2015-2018 Ford Transit Medium or High Roof
- Six inch pigtail with sync wire allows up to eight lightheads to be synchronized together for warning segment of the lighthead
- Amp Draw @ 12 VDC, Warning: 1.5/P, 0.60/A, Perimeter: 0.77/A
- Size: 4.29" (109mm) H x 2.25" (57mm) D x 6.75" (171mm) L

Warning Certified To:

- NFPA 1901 when properly configured
- ASTM / KKK 1822-F Upper and Lower
- NFPA 1917 2013 Edition Upper and Lower
 - Table 7.9.13.5 Optical Power Requirements Large Ambulance
 - Table 7.9.14.4 Optical Power Requirements Small Ambulance
- SAE J595
- SAE J845 Selective Coverage
- CAC Title XIII

Illumination Certified To:

- AMD 024 Perimeter Illumination Spec
 - M6V2 Two lightheads on each side of the vehicle
- NFPA 13.10.1.2 Ground Lighting
 - M6V2 One lighthead mounted up to 6'



M6V2R

MODELS

M6V2*	Surface
M6V2*C	Surface, with Clear outer lens

Replace * symbol in model number with LED color desired: A=Amber, B=Blue, C=White, R=Red







Elango	_	
Flange	Chrome	
Flange	Black	
15° Angled Surface Mount	Chrome	
Housing	Black	
Flange, Adapts M6 to 600 Series Mounting	Chrome Black, paintable to match vehicle	
Front Light Pod for Eight M6 Lightheads for the 2015-2018 Ford Transit Medium Roof		
Rear 2 Piece Light Pod for Six lightheads, 2015-2018 Ford Transit, Medium or High Roof		
Front Light Pod for Eight M6 Series Lightheads for the 2015- 2018 Ford Transit High Roof		
Brush Guard	Black	
	Flange 15° Angled Surface Mount Housing Flange, Adapts M6 to 600 Series Mounting Front Light Pod for Eight M6 Lightheads for the 2015-2018 Ford Transit Medium Roof Rear 2 Piece Light Pod for Six lightheads, 2015-2018 Ford Transit, Medium or High Roof Front Light Pod for Eight M6 Series Lightheads for the 2015- 2018 Ford Transit High Roof	



M9 V-Series™

FEATURES

- Models have 2-in-1 combination warning and scene lighting
- Surface mount
- Includes Chrome plated flange
- Adapter flange kit mounts M9 lightheads to upper sides of the 2015-2018
 Transit for 360° of critical coverage
- Warning segment has 21 Scan-Lock™ flash patterns
- Six inch pigtail with sync wire allows up to eight lightheads to be synchronized together for the warning segment of the lighthead
- Amp Draw @ 12 VDC, Warning 2.4/P, 0.96/A, Scenelight: 2.4/A
- Size: 6.5" (165mm) H x 2.60" (66mm) D

Warning Certified To:

- NFPA 1901 when properly configured
- ASTM / KKK 1822-F Upper and Lower
- NFPA 1917 2013 Edition Upper and Lower
 - Table 7.9.13.5 Optical Power Requirements Large Ambulance
 - Table 7.9.14.4 Optical Power Requirements Small Ambulance
- SAE J595
- SAE J845 Selective Coverage
- CAC Title XIII

Illumination Certified To:

- AMD 024 Perimeter Illumination Spec
 - M9V2 One lighthead on each side of the vehicle
- NFPA 13.10.1.1 Ground Lighting
 - M9V2 Two lightheads



MODELS

M9V2*	Surface
M9V2*C	Surface, with Clear outer lens

Replace * symbol in model number with letter indicating color desired; A=Amber, B=Blue, R=Red, C=White







OPTIONS

M9VFC900	Flange, adapts M9V to 900 Series mounting	Chrome
M9BRUSH	Brush Guard	Black

2015-2018 Ford Transit Mounting Options

Upper Side Ada	Upper Side Adapter Flange Kit*		
Medium Roof			
M9HTM5FC	Front Driver & Passenger Side	Chromo	
M9HTM5RC	Rear Driver & Passenger Side	Chrome	
High Roof			
M9HTH5FC	Front Driver & Passenger Side	Chrome	
M9HTH5RC	Rear Driver & Passenger Side		

^{*}Two M9 or M9V Series Lightheads Purchased Separately



51 Winthrop Road Chester, Connecticut 06412-0684 (860) 526-9504 www.whelen.com

